

# BOSTIK® Hardwood Products

## PRODUCT INFORMATION

# BOSTIK 1100 FS

## POLYURETHANE ADHESIVE SEALANT

### PRODUCT DESCRIPTION

Bostik's 1100 FS is a fast setting, one-part, moisture cure, waterproof, gun grade adhesive. Once cured, its superior elastomeric properties provide a tough, flexible, tenacious bond to a variety of surfaces.

### TYPICAL APPLICATION

Please refer to current Bostik's Best or Ultra-Set Hardwood Product Information sheets for typical applications and compatibility information.

### SHELF LIFE

One year from date of manufacture, in unopened original containers. Store in cool, dry temperatures at 80° Fahrenheit or less.

### CLEAN UP

Excess adhesive should be dry-wiped from all surfaces and tools while still uncured. Commercial solvents, such as mineral spirits, may be used.

Please Note: Cured adhesive is difficult to remove without altering or damaging the surface to which the adhesive was applied.

### PHYSICAL PROPERTIES

#### Uncured

Tool/Work Life	70 Minutes	Bostik Test Method
Tack Free Time	90 Minutes	ASTM C 679
Curing Time	1.5-3 Days	Varies w/relative humidity
Flow, Sag, Slump	Nil	ASTM C 639

#### After 7 days cure at 77° Fahrenheit and 50% RH

Hardness (Shore A)	41	ASTM D 2240
Tensile Strength	301 PSI	ASTM D 412
Elongation	850%	ASTM D 412
Adhesion in Peel	>25 piw	ASTM C 794

### PACKAGING

Bostik 1100 FS Fast Set is available in 10.3 fl.oz. cartridges. 12/case 13 lbs./case.

### COLORS

Bostik 1100 FS is available in the following standard colors: White and Gray.



**Bostik Findley, Inc.**

Middleton, MA 01949

800/7-BOSTIK or

888/592-8558

**TECHNICAL SERVICE**

800-523-6530

### MANUFACTURING LOCATIONS

Temecula, CA 92590

Conyers, GA 30207

Twinsburg, OH 44087

Paulsboro, NJ 08066

#### LIMITED WARRANTY

All statements, technical information, and recommendations set forth herein, are based on tests which BostikFindley, Inc. believes to be reliable. However, BostikFindley, Inc. does not guarantee their accuracy or completeness. The buyer should conduct his/her own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley, Inc's order acknowledgement. Bostik Findley, Inc. warrants that the product conforms with BostikFindley, Inc's written specifications, and is free from defects. BOSTIK FINDLEY'S DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.